

Model		New Generation AC-DC 1Ø Input DIN Rail		Old Generation AC-DC 1Ø Input DIN Rail				
		 XDR <small>COMING SOON</small> High-End Flagship Ultra Slim & High Reliability DIN Rail	 XDR-E <small>NEW</small> Cost-Effective Ultra Slim DIN Rail	SDR High Performance DIN Rail	NDR Mid-Grade DIN Rail	EDR Low-Grade DIN Rail		
Vin		85~305Vac	85~264Vac	88~264Vac	90~264Vac			
Inrush Current		<10A / 230Vac	< 30A~35A / 230Vac (by model)	<50A~80A / 230Vac (by model)	<40A / 230Vac			
Vout		12V, 24V, 36V, 48V (XDR-960 without 12V)	12V, 24V, 36V, 48V (XDR-960E without 12V)	12V, 24V, 48V (SDR-240~960 without 12V)	12V, 24V, 48V (NDR-240/480 without 12V)	12V, 24V, 48V (EDR-150 without 12V/48V)		
Output Wattage		75W / 120W / 240W / 480W / 960W 200% peak power 600% peak current	75W / 120W / 150W / 240W / 480W / 960W	75W / 120W / 240W / 480W / 960W 130% peak power	75W / 120W / 240W / 480W		75W / 120W / 150W	
Efficiency		89% ~ 96% (by model)		88.5% ~ 94% (by model)	85.5% ~ 92.5% (by model)		85% ~ 88.5% (by model)	
Parallel Function		3840W (3+1) (XDR-240~960)	3840W (3+1) (XDR-480E/960E)	3840W (3+1) (SDR-480/960)	N/A			
Communication		MODbus (XDR-240~960)	N/A	N/A	N/A			
DC OK Relay Contact		V		V	N/A			
Remote Control		V (XDR-240~960)	N/A	N/A	N/A			
ORing FET		V (XDR-120~960)	N/A	N/A	N/A			
Operating Temp.		-40~+85°C (>+60°C derating)	-40~+70°C (>+50°C derating)	-30~+70°C (>+50°C derating)	-20~+70°C (>+50°C derating)	-20~+60°C (>+50°C derating)		
OVC Level		OVC III		N/A				
PCB Conformal Coating		V	N/A	N/A				
Safety Certification		CB / TUV / UL / RCM / BSMI / CCC BIS / EAC / KC / CE / UKCA DNV / C1D2 / SEMI47 (BIS/KC certified , no stock by request)	CB / TUV / UL / RCM / BSMI / CCC BIS / EAC / KC / CE / UKCA (BIS/KC certified , no stock by request)	CB / TUV / UL / RCM / EAC / CE / UKCA BSMI (SDR-120~960) KC (SDR-960)	CB / TUV / UL / RCM / EAC / CE / UKCA BSMI (NDR-480) BIS (NDR-240/480)	CB / TUV / UL / RCM / EAC / CE / UKCA BSMI (EDR-120/150) BIS (EDR-120)		
		62368-1 + 61010-1 + 61558-1			62368-1			
EMC	EMI	EN55032 Class B		EN55032 Class B		EN55032 Class A		
	ESD	Contact ± 8KV Air ± 15KV	Contact ± 4KV Air ± 8KV	Contact ± 4KV Air ± 8KV				
Dimension (W x H x D)	75W	30 x 125.2 x 116 mm (-23%)		32 x 125.2 x 102 mm				
	120W	30 x 125.2 x 116 mm (-23%)		40 x 125.2 x 113.5 mm				
	150W	-	30 x 125.2 x 116 mm (-23%)	-		40 x 125.2 x 113.5 mm		
	240W	40 x 125.2 x 116 mm (-35%)		63 x 125.2 x 113.5 mm		-		
	480W	48 x 125.2 x 125 mm (-45%)		85.5 x 125.2 x 128.5 mm				
	960W	96 x 125.2 x 132 mm (-23%)		110 x 125.2 x 150 mm	-			
Terminal Block Type		Screw Terminal	Push In	Lever Actuated	Screw Terminal	Screw Terminal		
								
Warranty		5 Years	3 Years	3 Years		2 Years		

※ XDR is the flagship model, while XDR-E is the cost-effective model.

※ XDR-E can replace SDR / NDR / EDR. For higher specification requirements, advanced communication interfaces, marine/semi-conductor/explosion-proof safety certifications, alternative wiring methods, and a 5-year warranty, it is recommended to choose the flagship model-XDR.

※ Compared to SDR / NDR / EDR, XDR / XDR-E offers superior specifications, more comprehensive safety certifications, a more compact size, a wider selection of terminal blocks, and a longer warranty. For new projects, please adopt the XDR / XDR-E series.